



*304.015 QUARTZ GRILL/SALAMANDER - MANUAL

Use and Installation Manual TS 3270

Presentation of the equipment

Unique in the world, this real toaster salamander with 2 levels and 3 quartz tubes levels contains 2 GN1/1 to defrost, brown, glaze, grill or toast.

The infrared quartz tubes provide an immediate cooking facility without a preheating period (ca. 400 toasts/hour) without smoke or smell transmission.

They are made with stainless steel fitted with an adjustable cooking.

Dimensions and capacity

	TS 3270
Outside Dimensions	640x380x475
Power W	4000
Volts V	380 V
	3PH + N + T
Weight Kg	18,5
Toasts/H	400
Heating elt.	9

Working

Our toasters are fitted with :

- ◆ 4 positions commutator
- ◆ 15 minutes timer with lock position for non stop use
- ◆ 1 red pilot light
- ◆ 1 green pilot light

Cooking with infrared radiations does not require pre-heating.

Warning: for safety reasons, your products should always work with the drip tray.

Cleaning

Before cleaning, turn your appliance off the mains and let it cool.

Do not allow the skin to come into contact with quartz tubes.

Clean the tubes with a cloth spacked with alcohol.

Do regularly clean the metallic walls of your appliance with a wet sponge and some washing-up liquid.

Grills should not be washed with an abrasive sponge.

Do not wash your appliance under running water as filtering might damage it.

Installation

You must not put the lateral sides of your appliance close to a wall or a partition made in a combustible material.

A 30 cm distance from the partition level is recommended.

Electrical connection

This appliance should be connected in three phases with neutral.

Explanation for the wires colors :

Live 1:	Brown
Live 2:	Black
Live 3:	Grey
Neutral:	Blue
Earth:	Yellow-green